

Fiber Optic Tools

Drop Cable Stripper

Material	Metal
Color	Dark Green
Suitable Fiber	125µm
Suitable Fiber Coating	250µm
Number of Fiber Core	1-2



Miller Cable Stripper-CFS3

1. For stripping 250 micron buffer coating to expose 125 micron cladded fiber
2. 140 µm diameter hole and Vopening in blade allows removal of 250 micron buffer coating from 125 micron fiber
3. Second hole for stripping 2-3 mm fiber jackets
4. Pre-set at the factory—no adjustments needed
5. Will not scratch or nick glass fiber
6. All surfaces are precise tolerances to assure clean, smooth strips
7. Comfort-grip, ergonomic handles
8. Lock to hold tool closed when it is not in use
9. Length: 6.5 in (165 mm); Weight: 4.2 oz (119 g)



Fiber Optic Visual Fault Locator

Model	VFL-500 Series
Central wavelength	650nm±10nm
Emitter type	FP-LD
Output power	5mw, 10mw, 20mw, 30mw
Operating model	Both CW and Pulse available
Pulse frequency	3 Hz to 9 Hz
Power supply	2AAA alk aline batteries
Operating temperature	-20°C to 60 °C
Storage temperature	-40°C to 85 °C
Dimension	-FL-005 Φ13 X 67



Cleaner Pen

Fiber Optic Cleaner Pen is designed to specially work well with the female connectors, this instrument cleans the ferrule end faces removing dust, oil, and other debris without nicking or scratching the end face.
 FC/SC/ST Cleaner Pen, universal 2.5mm;
 LC/MU Cleaner Pen, universal 1.25mm.



Fiber Optic Cleaning Cloths

Name	Kimtech Fiber Optic Cleaning Wipes
Material	100% woodpulp
Weight	20g/m2
Ply	1 Ply
Color	White
Size	110mm*210mm



Mid-Span Access Tool

Name	Mini-Span Access Tool	
Model	CFS-05	
Striping diameter	1.5mm-3.3mm	
Loose tube diameter	1.5-1.9mm	2.0-2.4mm
	2.5-2.9mm	3.0-3.3mm
Blade Material	Characteristics Alloy	
Color	Black	
Product Size	50mm*40mm*18mm	
Package Size	75mm*60mm*18mm	



Stainless Steel Strapping Tool

1. Weight: 1.2kg
2. Suit for width: 6.4-20mm steel band
3. Use with: Stainless Steel Cable Tie-Ball Self-locking Type
Stainless Steel Cable Tie-Y Ear lock Type
Stainless Steel Cable Tie-Wing lock L Type
Stainless Steel Cable Tie-SC lock Type

