

Dome Fiber Optic Cable Closure 96FO



Description

Suitable for aerial, cable duct, direct buried, pedestal and provides the perfect solutions for the protection of fiber splice points from the environment. Suitable for multi-customer cables export, give a better solution for FTTH project.

Features

1. High quality engineering plastic, long service life
2. Reliable gasket sealing system, rated to IP68
3. High compressive strength.
4. Multi-cables are allowed to pass through a same port with mechanical lock.
5. Suitable for aerial, wall, manhole and pole mounted.

Specification

| | |
|---|----------------------|
| Dimensions (mm) | 460×168×200mm |
| Numbers of Cable ports | 1 oval 4 round |
| Cable diameter (Max.) | Ø8-16mm, Ø8-25mm |
| Splice tray capacity | 4/24FO |
| Maximum numbers of the splice tray | 4 pcs |
| Splice capacity in total | 96 FO |
| Circular ports | 4×Ø25mm |
| Oval Port | 1 inlet port×80*40mm |



Contact us: info@linkplus.com.es

Performance

| | |
|-----------------------------------|------------------------|
| Material | Modified polycarbonate |
| Temperature range | -40 °C to +70 °C |
| Life expectancy | 20 years |
| UV resistant additives | 5% |
| Flame resistant | V1 |
| Seal material of the box | Rubber |
| Seal material of the ports | Rubber |
| Protection rating | IP68 |